APPARATUS AND METHOD FOR SELECTING PROGRAM HALTS IN AN UNPROTECTED PIPELINE AT NON-INTERRUPTIBLE POINTS IN CODE EXECUTION

This application claims priority under 35 USC §119(e)(1) of Provisional Application Number 60/434,231 (TI-34657P) filed December 17, 2002.

Related Applications

U.S. Patent Application (Attorney Docket No. TI-34654), entitled APPARATUS AND METHOD FOR SYNCHRONIZATION OF TRACE STREAMS FROM MULTIPLE PROCESSORS, invented by Gary L. Swoboda, filed on even date herewith, and assigned to the assignee of the present application; U.S. Patent Application (Attorney Docket No. TI-34655), entitled APPARATUS AND METHOD FOR SEPARATING DETECTION AND ASSERTION OF A TRIGGER EVENT, invented by Gary L. Swoboda, filed on

even date herewith, and assigned to the assignee of the present application; U.S. Patent Application (Attorney Docket No. TI- 34656), entitled APPARATUS AND METHOD FOR STATE SELECTABLE TRACE STREAM GENERATION, invented by Gary L. Swoboda, filed on even date herewith, and assigned to the assignee of the present application; U.S. Patent Application (Attorney Docket No. TI-34658), entitled APPARATUS AND METHOD FOR REPORTING PROGRAM HALTS IN AN UNPROTECTED PIPELINE AT NON-INTERRUPTIBLE POINTS IN CODE EXECUTION, invented by Gary L. Swoboda, filed on even date herewith, and assigned to the assignee of the present application; U.S. Patent Application (Attorney Docket No. TI-34659), entitled APPARATUS AND METHOD FOR A FLUSH PROCEDURE IN AN INTERRUPTED TRACE STREAM, invented by Gary L. Swoboda, filed on even date herewith, and assigned to the assignee of the present application; U.S. Patent Application (Attorney Docket No. TI-34660), entitled APPARATUS AND METHOD FOR CAPTURING AN EVENT OR COMBINATION OF EVENTS RESULTING IN A TRIGGER SIGNAL IN A TARGET PROCESSOR, invented by Gary L. Swoboda, filed on even date herewith, and assigned to the assignee of the present application; U.S. Patent Application (Attorney Docket No. TI-34661), entitled APPARATUS AND METHOD FOR CAPTURING THE PROGRAM COUNTER ADDRESS ASSOCIATED WITH A TRIGGER SIGNAL IN A TARGET PROCESSOR, invented by Gary L. Swoboda, filed on even date herewith, and assigned to the assignee of the present application; U.S. Patent Application (Attorney

Docket No. TI-34662), entitled APPARATUS AND METHOD DETECTING ADDRESS CHARACTERISTICS FOR USE WITH A TRIGGER GENERATION UNIT IN A TARGET PROCESSOR, invented by Gary Swoboda and Jason L. Peck, filed on even date herewith, and assigned to the assignee of the present application; U.S. Patent Application (Attorney Docket No. TI-34663), entitled APPARATUS AND METHOD FOR TRACE STREAM IDENTIFICATION OF A PROCESSOR RESET, invented by Gary L. Swoboda, Bryan Thome and Manisha Agarwala, filed on even date herewith, and assigned to the assignee of the present application; U.S. Patent (Attorney Docket No. TI-34664), entitled APPARATUS AND METHOD FOR TRACE STREAM IDENTIFICATION OF A PROCESSOR DEBUG HALT SIGNAL, invented by Gary L. Swoboda, Bryan Thome, Lewis Nardini and Manisha Agarwala, filed on even date herewith, and assigned to the assignee of the present application; U.S. Patent Application (Attorney Docket No. TI-34665), entitled APPARATUS AND METHOD FOR TRACE STREAM IDENTIFICATION OF A PIPELINE FLATTENER PRIMARY CODE FLUSH FOLLOWING INITIATION OF AN INTERRUPT SERVICE ROUTINE; invented by Gary L. Swoboda, Bryan Thome and Manisha Agarwala, filed on even date herewith, and assigned to the assignee of the present application; U.S. Patent Application (Attorney Docket No. TI-34666), entitled APPARATUS AND METHOD FOR TRACE STREAM IDENTIFICATION OF A PIPELINE FLATTENER SECONDARY CODE FLUSH FOLLOWING A RETURN TO PRIMARY CODE EXECUTION, invented by Gary L. Swoboda, Bryan Thome and Manisha Agarwala filed on even date

herewith, and assigned to the assignee of the present application; U.S. Patent Application (Docket No. TI-34667), entitled APPARATUS AND METHOD IDENTIFICATION OF A PRIMARY CODE START SYNC POINT FOLLOWING A RETURN TO PRIMARY CODE EXECUTION, invented by Gary L. Swoboda, Bryan Thome and Manisha Agarwala, filed on even date herewith, and assigned to the assignee of the present application; U. S. Patent Application (Attorney Docket No. TI-34668), entitled APPARATUS AND METHOD FOR IDENTIFICATION OF A NEW SECONDARY CODE START POINT FOLLOWING A RETURN FROM A SECONDARY CODE EXECUTION, invented by Gary L. Swoboda, Bryan Thome and Manisha Agarwala, filed on even date herewith, and assigned to the assignee of the present application; U.S. Patent Application (Attorney Docket No. TI-34669), entitled APPARATUS AND METHOD FOR TRACE STREAM IDENTIFICATION OF A PAUSE POINT IN A CODE EXECTION SEQUENCE, invented by Gary L. Swoboda, Bryan Thome and Manisha Agarwala, filed on even date herewith, and assigned to the assignee of the present application; U.S. Patent Application (Attorney Docket No. TI-34670), entitled APPARATUS AND METHOD FOR COMPRESSION OF A TIMING TRACE STREAM, invented by Gary L. Swoboda and Bryan Thome, filed on even date herewith, and assigned to the assignee of the present application; U.S. Patent Application (Attorney Docket No. TI-34671), entitled APPARATUS AND METHOD FOR TRACE STREAM IDENTIFCATION OF MULTIPLE TARGET PROCESSOR EVENTS, invented by Gary L. Swoboda and Bryan Thome, filed on even date herewith, and

assigned to the assignee of the present application; and U.S. Patent Application (Attorney Docket No. TI-34672 entitled APPARATUS AND METHOD FOR OP CODE EXTENSION IN PACKET GROUPS TRANSMITTED IN TRACE STREAMS, invented by Gary L. Swoboda and Bryan Thome, filed on even date herewith, and assigned to the assignee of the present application are related applications.

Background of the Invention

1. Field of the Invention

This invention relates generally to the testing of digital signal processing units and, more particularly, to the interruption of code execution to determine the status of various portion of the target processor implementing the code or to initiate a different code execution routine. A processor can have a protected pipeline or a non-protected pipeline. When the target processor has a non-protected pipeline, the code executing on the processor can have interruptible portions and can have non-interruptible portions.

2. Description of the Related Art

As microprocessors and digital signal processors have become increasingly complex, advanced techniques have been

developed to test these devices. Dedicated apparatus is available to implement the advanced techniques. Referring to Fig. 1A, a general configuration for the test and debug of a target processor 12 is shown. The test and debug procedures operate under control of a host processing unit **10**. The host processing unit **10** applies control signals to the emulation unit **11** and receives (test) data signals from the emulation unit **11** by cable connector **14**. The emulation unit **11** applies control signals to and receives (test) signals from the target processor **12** by connector cable **15**. The emulation unit **11** can be thought of as an interface unit between the host processing unit **10** and the target processor **12**. The emulation unit **11** must process the control signals from the host processor unit **10** and apply these signals to the target processor **12** in such a manner that the target processor will respond with the appropriate test signals. The test signals from the target processor **12** can be a variety types. Two of the most popular test signal types are the JTAG (Joint Test Action Group) signals and trace signals. The JTAG signal provides a standardized test procedure in wide use. Trace signals are signals from a multiplicity of junctions in the target processor **12**. While the width of the bus interfacing to the host processing unit **10** generally have a standardized width, the bus between the emulation unit **11** and the target processor **12** can be increased to accommodate the increasing complexity of the target processing unit **12**. Thus, part of

the interface function between the host processing unit **10** and the target processor **12** is to store the test signals until the signals can be transmitted to the host processing unit **10**.

In the test and debug of the target processor, specified internal events result in a halt of the target processor (i.e., for analysis of the configuration of the processor) or in a change of processor program execution. These specified events are monitored by dedicated apparatus. Upon detection of the occurrence of the event, the monitoring apparatus generates an event signal. The events signal or signals are applied to a trigger device. The trigger device issues a trigger signal that results in the change of operation of the target processor. Referring to Fig. 1B, the operation of the trigger generation unit **19** is shown. Monitoring apparatus **18**, including event signal generation units **181** through **18N**, is typically included in the target processor **12**. The event generation units **181** - **18N** each monitors some portion of the target processor to determine when a specified condition or event is present. When the specified condition is detected by the event signal generation unit monitoring the condition, an event signal is generated. The event signals are applied to the trigger generation unit **19**. Based on the event signals applied to the trigger generation unit **19**, a trigger signal is selected. Certain events and combination of events,

referred to as an event front, generate a selected trigger signal that results in certain activity in the target processor, e.g. a debug halt. Combinations of different events generating trigger signals are referred to as jobs. Multiple jobs can result in the same trigger signal or combination of trigger signals. In the test and debug of the target processor, the trigger signals can provide impetus for changing state in the target processor or for performing a specified activity. The event front defines the reason for the generation of trigger signal. This information is important in understanding the operation of the target processor because, as pointed out above, several combinations of events can result in the generation of a trigger signal. In order to analyze the operation of the target processing unit, the portion of the event front resulting in the trigger signal must be identified in order to determine the reason for the generation of the trigger signal.

A development system can create a number of test and debug events. These test and debug events halt the code execution so that analysis can be made of the state of the processor. In a real-time test and debug environment, it is desirable to allow the service of interrupt signals designated as real time interrupts to continue after a debug event generates an execution halt. Because the test and debug events are generally accepted at the next

instruction boundary, a test and debug event can halt the code execution at a non-interruptible point in the code execution.

In a protected pipeline, real-time interrupt procedures can occur at any instruction boundary, so it is not a problem that code execution halts in a non-interruptible point. Once the code execution is halted, real-time interrupt procedures continue even though the code was not interruptible at the point at which the code execution was halted. In other words, in a non-interruptible code portion, real time interrupt procedures can continue in a protected pipeline independent of whether code execution is halted at a non-interruptible point.

In an unprotected pipeline, the situation is much different than for a protected pipeline. In the unprotected pipeline, real time interrupts cannot occur at any arbitrary instruction boundary because of architectural problems (e.g., delayed branches in flight) or instruction-to-instruction relationships that can be disturbed (the global enable bit is disabled to indicate these code areas). Because the pipeline sequence must be preserved in an unprotected pipeline, this rule must also be obeyed when code execution is halted by a test and debug event.

When a test and debug event is allowed to halt code execution in an unprotected pipeline at a non-interruptible point in the code execution, real time interrupt services must be blocked because these activities would corrupt the code so that the code execution could not be resumed after the interrupt return. To preserve the ability to service real-time interrupts after code execution halts, test and debug events must be blocked until code execution reaches an interruptible point.

However, an application developer may find it desirable to halt the code execution at a non-interruptible point in the code to observe the machine state even though real-time interrupt are blocked, and other times, may find it desirable to delay code execution halts to points where the code is interruptible (i.e., allowing service of real time interrupts after execution halts.

A need has therefore been felt for apparatus and an associated method having the feature that a program execution halt can be taken in a non-protected pipeline during a non-interruptible portion of the code. It would be further feature of the apparatus and associated method to permit a user to select whether a program execution halt can be performed in a protected pipeline during execution of non-interruptible code portion. It would be yet another feature of the apparatus and the associated method to

permit a program execution halt during either a protected portion of the program execution or an unprotected portion of the program code execution in a protected pipeline.

Summary of the Invention

The aforementioned and other features are accomplished, according to the present invention, by providing a storage unit for storing a signal indicating that the program execution halt can be implemented in an unprotected pipeline whether the code is interruptible or non-interruptible. When the signal is present in the storage unit, a halt request will be forwarded immediately thereby resulting in a code execution halt. When the signal is not present in the storage unit, the halt request signal will be forwarded only during an interruptible portion of the code execution. The signal can be stored in the storage unit by the program or by the intervention through the test and debug facilities.

Other features and advantages of present invention will be more clearly understood upon reading of the following description and the accompanying drawings and the claims.

Brief Description of the Drawings

Figure 1A is a block diagram of the apparatus used in the test and debug of a target processor; while Figure 1B illustrates the generation of trigger signals.

Figure 2 is a block diagram of the apparatus for forwarding a halt signal during a non-interruptible code execution portion in a non-protected pipeline according to the present invention.

Description of the Preferred Embodiment

1. Detailed Description of the Figures

Fig. 1A and Fig. 1B have been discussed with respect to the related art.

Referring to Fig. 2, the apparatus for selectively halting code execution in a processor having a non-protected pipeline is shown. Storage unit **20** has a CONTROL signal applied thereto. When the CONTROL signal is stored in the storage unit **20**, a signal is applied to a first terminal of logic OR gate **22**. A second terminal of logic OR gate **22** has a signal indicating whether the executing code is currently in an interruptible or in a non-interruptible code portion. The output terminal of logic OR gate **22** is coupled to a first input terminal of logic AND gate **21**. A second terminal of logic AND gate **21** has a HALT REQUEST signal applied thereto. A HALT signal is generated at the output terminal of logic AND gate **21**.

2. Operation of the Preferred Embodiment

The operation of the present invention can be understood as follows. In a processing system having a non-protected pipeline, when a CONTROL signal is not stored in the storage unit **20** and a HALT REQUEST signal is applied to the second terminal of the logic AND gate **21**, then a HALT signal will be applied to the output terminal of logic AND gate **21** only when a positive INTERRUPTIBLE CODE PORTION signal is applied to the second input terminal of logic OR gate **22**. When the INTERRUPTIBLE CODE PORTION signal and the CONTROL signal are not present, then the HALT REQUEST signal will not result in a HALT signal. However, when the CONTROL signal is stored in storage unit **20**, a CONTROL signal is applied to an input terminal of logic OR gate **22** and a signal is applied to the first input terminal of logic AND gate **21**. In this situation, a HALT REQUEST signal will provide a HALT signal whether the INTERUPTIBLE CODE PORTION signal is present or not.

In this manner, a HALT signal can be generated even when a non-interruptible code portion is being executed. Furthermore, the code execution in a non-interruptible code portion is determined by the storage of the CONTROL signal in the storage unit. Therefore, the generation of a HALT REQUEST signal is under the control of the user testing or debugging the target processor.

While the invention has been described with respect to the embodiments set forth above, the invention is not necessarily limited to these embodiments. Accordingly, other embodiments, variations, and improvements not described herein are not necessarily excluded from the scope of the invention, the scope of the invention being defined by the following claims.